



DV 818-1550-60

High Voltage Diode

Properties

- Low forward voltage drop
- Low recovery charge
- High operating temperature
- Low leakage current

Applications

- Rectifier bridges

Key Parameters

V_{RRM}	=	6 000 V
I_{FAVm}	=	1 551 A
I_{FSM}	=	17 500 A
V_{TO}	=	1.047 V
r_T	=	0.399 mΩ

Types

	V_{RRM}
DV 818-1550-60	6 000 V
DV 818-1550-58	5 800 V
DV 818-1550-56	5 600 V
Conditions: $T_j = -40 \div 150 \text{ }^\circ\text{C}$, half sine waveform, $f = 50 \text{ Hz}$	

Mechanical Data

F_m	Mounting force	22 ± 2	kN
m	Weight	0.46	kg
D_s	Surface creepage distance	30	mm
D_a	Air strike distance	20.5	mm




Fig. 1 Case

Polovodice, a.s.

Novodvorska 1768/138a, 142 21 Praha 4, Czech Republic

tel.: +420 261 306 265, fax: +420 261 306 307, <http://www.polovodice.cz/>

Maximum Ratings			Maximum Limits	Unit
V_{RRM}	Repetitive peak reverse voltage $T_j = -40 \div 150 \text{ }^\circ\text{C}$	DV 818-1550-60 DV 818-1550-58 DV 818-1550-56	6 000 5 800 5 600	V
I_{FAVm}	Average forward current $T_c = 85 \text{ }^\circ\text{C}$		1 551	A
I_{FRMS}	RMS forward current		2 436	A
I_{RRM}	Repetitive reverse current, $V_R = V_{RRM}$		75	mA
I_{FSM}	Non repetitive peak surge current $V_R = 0 \text{ V, half sine pulse, } T_j = 25 \text{ }^\circ\text{C}$	$t_p = 8.3 \text{ ms}$	20 300	A
		$t_p = 10 \text{ ms}$	19 000	A
	Non repetitive peak surge current $V_R = 0 \text{ V, half sine pulse}$	$t_p = 8.3 \text{ ms}$	18 700	A
		$t_p = 10 \text{ ms}$	17 500	A
I^2t	Limiting load integral $V_R = 0 \text{ V, half sine pulse, } T_j = 25 \text{ }^\circ\text{C}$	$t_p = 8.3 \text{ ms}$	1 710 000	A ² s
		$t_p = 10 \text{ ms}$	1 805 000	A ² s
	Limiting load integral $V_R = 0 \text{ V, half sine pulse}$	$t_p = 8.3 \text{ ms}$	1 450 000	A ² s
		$t_p = 10 \text{ ms}$	1 531 250	A ² s
$T_{jmin} - T_{jmax}$	Operating temperature range		-40 \div 150	$^\circ\text{C}$
T_{STG}	Storage temperature range		-40 \div 150	$^\circ\text{C}$

Unless otherwise specified $T_j = 150 \text{ }^\circ\text{C}$

Characteristics		Value			Unit
		min	typ	max	
V_{T0}	Threshold voltage $I_{F1} = 2\,435 \text{ A, } I_{F2} = 7\,304 \text{ A}$			1.047	V
r_T	Forward slope resistance			0.399	m Ω
V_{FM}	Maximum forward voltage $I_{FM} = 4\,000 \text{ A}$			2.680	V
Q_{rr}	Recovered charge $V_R = 100 \text{ V, } I_{FM} = 2\,000 \text{ A, } di_F/dt = -30 \text{ A}/\mu\text{s}$		4 000		μC

Unless otherwise specified $T_j = 150 \text{ }^\circ\text{C}$

Thermal Parameters			Value	Unit
R_{thjc}	Thermal resistance junction to case	double side cooling	15	K/kW
		anode side cooling	24	
		cathode side cooling	40	
R_{thch}	Thermal resistance case to heatsink	double side cooling	4	K/kW
		single side cooling	8	

Transient Thermal Impedance

Analytical function for transient thermal impedance

$$Z_{thjc} = \sum_{i=1}^5 R_i (1 - \exp(-t/\tau_i))$$

Conditions:

$F_m = 22 \pm 2$ kN, Double side cooled

Correction for periodic waveforms

180° sine:	1.3 K/kW
180° rectangular:	1.7 K/kW
120° rectangular:	2.9 K/kW
60° rectangular:	4.8 K/kW

i	1	2	3	4	5
τ_i (s)	0.6937	0.2040	0.0452	0.0040	0.0005
R_i (K/kW)	6.04	3.83	3.76	1.31	0.07




Fig. 2 Dependence transient thermal impedance junction to case on square pulse




Fig. 3 Maximum forward voltage drop characteristics




Fig. 4 Surge forward current vs. pulse length, half sine wave, single pulse, $V_R = 0 V, T_j = T_{jmax}$




Fig. 5 Surge forward current vs. number of pulses, half sine wave, $T_j = T_{jmax}$




Fig. 6 Forward power loss vs. average forward current, sine waveform, $f = 50 \text{ Hz}$, $T = 1/f$




Fig. 7 Forward power loss vs. average forward current, square waveform, $f = 50 \text{ Hz}$, $T = 1/f$




Fig. 8 Max. case temperature vs. aver. forward current, sine waveform, $f = 50 \text{ Hz}$, $T = 1/f$




Fig. 9 Max. case temperature vs. aver. forward current, square waveform, $f = 50 \text{ Hz}$, $T = 1/f$

Notes

Polovodice, a.s., Novodvorska 1768/138a, 142 21 Praha 4, Czech Republic

Polovodice, a.s. reserves the right to change the data contained herein at any time without notice